



SECMAIR
FAYAT GROUP

SERVIRROUTE

MULTI-FUNCTION SPRAYER



Serviroute: the sprayer in all its forms

The Serviroute sprayer was designed for hot mix teams. The amount of time a traditional sprayer is used on this type of work is very low if it is only used to spray the tack coat. This is why Secmair has designed a multi-function machine that can be configured to the needs of each user. The Serviroute is available on a fixed or removable chassis (twist-lock or hook lift).

The tack coat remains the Serviroute's main function. Depending on requirements, a spray bar of up to 4.50 metres is available.

The re-supply of machinery with water and fuel (compactors, pavers, milling machines, etc.) is also available. The tank capacities are modular depending on the chassis and options. The maximum liquid capacity is 8 to 9,000 litres for a 2 axle chassis.

A large, lockable box can be used to secure the fuel tanks and tools for work (pneumatic drill, signs, tools, etc.).

Other options are also available (sweeper, water spraying bar, handling skip and arm to stow paver extensions, bar and gritter for joint sealing between two layers of mix, etc.).



Tack coat



Secure storage box

On site machinery supply



Water bar (option)



Control station

Additive bar (option)



Extension bar (option)

Serviroute R for surface dressing work

The Serviroute R sprayer is designed to work on medium sized surface dressing works. Its binder circuit design and its computerised dosage coupling make it possible to guarantee much higher spraying accuracy than what is required by the standard - Test standard on test bench: NF P 98 726.

A wide dosage range

Surface dressing and pre-mix tack coats do not have the same spraying requirements. The Serviroute can spray both small doses (300 g/ m²) on narrow widths and high doses at full width (3 kg/m²) while maintaining a constant working speed.

A highly intuitive and robust operating system is used to manage the dosage from the cabin.

Additive bars

The use of additives is increasingly common both for surface dressing and tack coats.

As an option, the Serviroute can be fitted with bars in front of and/or behind the binder in order to spray all types of additive.

Compact design for optimal working load, together with safe maintenance

The large numbers of machines and reduced work site space requires highly compact machines. The overhang and the wheel base are the shortest on the market. The maximum height is at the truck cabin level. The working load is also optimised.

Daily servicing - filter cleaning, access to pneumatic, electric and hydraulic parts, is now 100% possible from the ground.



Towing hook (option)



Compact design for optimal working load

Easy maintenance and servicing



Servicing access from the ground